

FT-125 X3 Fountain

Two people are recommended for the installation of this fountain!



Pump Kit Parts List

PK300 pump (1)
#10 stopper (1)
Approx. 3" length of 5/8" Clear tubing (3) **
Approx. 6" length of 1/2" Black Non-Kink tubing (2) **
Wedges (2)
Hose clamps (2)

* Hose clamps may be used as flow restrictors

**Black non-kink tubing and clear vinyl tubing have been preassembled

FOUNTAIN INFORMATION:


This fountain holds approximately 5 gallons of water.

This fountain uses a medium fountain cover.
(FTNCOV-MED)

Compatible with Refill #10 Device and LED Kits
(A different style stopper may be requested for these parts.)

TOOLS REQUIRED:

Bubble Level



PUMP INFORMATION:

OEMPF320 - 320 GPH Pump
16 FT cord length

- W I N T E R C A R E -

Fountain bowls/tops and other fountain components, which collect water, should not be left outside in the winter since any component, which fills with water and freezes may crack. Likewise, components such as pedestals, which remain in a basin, filled with water, which then freezes, may also crack or crumble. Ideally, therefore, a fountain should always be stored indoors or in a dry protected place such as a covered porch away from the elements. However, if a fountain must be left outside:

- (1) Remove pump, rubber stoppers, drainpipes, finials, and other small components for storage indoors. Note that stoppers or drainpipes are removed to allow drainage in the event water accumulates in any basin.
- (2) Raise fountain base from ground with wood strips so that base will not freeze to the ground surface.
- (3) Cover or wrap the fountain with burlap or other absorbent material (old blanket or towel) and then cover securely with plastic, making sure that water will not accumulate in the basin or other fountain component and freeze;
- (4) Check fountain periodically to insure that plastic is secure and water is not accumulating in any fountain component.

- G E N E R A L F O U N T A I N T I P S -

Install fountains on a level surface. You will need a properly grounded 110-volt (AC only) GFCI protected receptacle near the fountain for your pump. All pumps are submersible and must be completely underwater to function properly. Test all pumps and adjust to full output prior to assembly. It is not recommended that fountains be placed directly on grass or dirt. Position the channel opening at the base of each fountain toward the electrical outlet to be used since the pump cord will be threaded through this opening.

All of our cast stone is proudly



Made in USA


Check out YouTube for a "How to" video.

For more Campania product information visit www.campaniainternational.com

FT-125 X3 Fountain


Two people are recommended for the installation of this fountain!

Assemble your fountain on a level surface capable of holding a minimum of 547 pounds with an approximate 1.5 square foot footprint.




FT-125A (274 lbs)
36"L x 3.75"W x 32"H

1. Stand up the water feature (FT-125A) placing it into position where the fountain will be installed.
 - a. NOTE - If placing against a wall leave enough space to pass your hand behind it. The fountain can be moved back after pump installation is completed and the cord has been run behind the fountain.




FT-125D (69 lbs)
20"L x 10.5"W x 6"H

2. Place the bottom rectangle (FT-125D) against the water feature, centered underneath the rectangular opening in the water feature (FT-125A).




FT-125B (148 lbs)
28"L x 13.75"W x 10"H

3. Center the basin (FT-125B) on the support block (FT-125D), but do not fit into water feature (FT-125A) yet.
4. Assemble the pump kit.
 - a. Attach the 1/2" end of the preassembled tubing with only one piece of clear tube to the pump outlet.
 - b. Place the stopper around the pump cord approximately 6" from the pump.
5. Feed the pump cord through the hole in the basin (FT-125B).
6. **FIRMLY** press the stopper into the hole evenly.
7. Attach the loose end of the tubing to the CPVC pipe protruding inside the basin.
8. Take the second piece of tubing and attach each end to the CPVC pipes protruding at the back of the basin (FT-125B) and the top of the cut out in the back of the feature (FT-125A).
9. Push basin into position in the hole.
 - a. NOTE – The basin will only go up to a 1/4" inside water feature hole.
10. Check sides of basin so that gaps on both sides against water feature are even.



FT-125C (9 lbs)
9.25"L x 4.25"W x 4.5"H

11. Place pump cover (FT-125C) in place over the pump and the cord.



A-375 (3 lbs) - A-376 (1 lb)
6"L x 5.25"W x 3"H
5.75"L x 3"W x 2.25"H

12. Place the bird statues (A-375 and A-376) anywhere on the fountain.
 - a. Note: If you want to secure them into place, you may use 100" clear silicone.
13. Fill the fountain with water.